

Limit plug gauges DIN2245 Express

(Go + NoGo)

Ø 3,001-6,000/0,001mm

Product 1081302ex
number:

EAN / 4066918009432

GTIN:

Customs 90318020

code:

Delivery Parcel delivery service

method:

Weight: 0.03kg



Product description

- DIN 2245 until Ø 65.000mm (GO and NO-GO sides on one gauge)
- DIN 2246 / 2247 > Ø 65.000mm (Separate GO and NO-GO sides, pair)
- ISO Tolerance A-ZC, Qualities >= 6, all intermediate dimensions, all numerical tolerances up to and including tolerance quality IT6
- GO and NO-GO side, Hardened tool steel
- GO side with wear allowance (workshop gauge)

Delivered in individual packages

1081 2..zm: Regular delivery time

1081 3..ex : Express Service, ULTRA fast delivery

! Order notice - Please enter exact nominal diameter, e.g. Ø 7.58mm or Ø 20.495mm, as well as the required tolerance e.g. H6 or 0/+0.05mm

! Measuring faces + handles in special shape, master gauges and larger lengths not possible in fast service.

! TIN- and TICN-coated limit plug gauges, master gauges without wear allowance and measuring faces in special shapes on request.

Diamond Graphite coating for limit plug gauges from Ø 3mm on request. Advantages: Longer service life, corrosion resistant, low friction and wear resistant. This coating is not possible for master gauges.

Technical Data

Size:	Ø 3,001-6,000/0,001mm
Article no.:	1081302ex
Brand:	ULTRA
Express service:	YES
Material:	Hardened steel
Nominal size:	Ø 3,001-6,000mm
Step:	0,001mm
Weight:	0.03kg