

Digital pistol grip bore gauge sets, 3-point XT GROOVE for groove meas., incl. setting rings & UKAS calibration 6-20/0,001/58/62mm Bluetooth

Product number: 2510607b

Manufacturer number: SP-SXTH10M-BT-GRO

Customs code: 90173000

Delivery method: Parcel delivery service

Weight: 2.7kg



Product description

- DIN 863
- Protection class IP67, Sylvac System
- Stepped hardened steel measuring faces
- Minimum entry-Ø for groove profile: 0.3mm below minimum
- When used with a depth stop, the groove heads can be used to measure plain bores as well as grooves
- Pistol handle
- Large LCD display
- With Bluetooth function and SylvacBT Smart App for a wireless data transmission
- Constant measuring force, spring loaded

Delivered in a case, including setting rings, UKAS calibration certificate and depth stops

Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function \pm
- Max. / min. memory
- Hold function
- Data output Proximity

Contents:

- 1 piece Digital readout unit with pistol grip
- 5 pieces measuring heads (1 piece of each measuring range 6-8 / 8-10 / 10-12.5 / 12.5-16 / 16-20mm)
- 3 pieces setting rings (1 piece of each Ø 8 / 12.5 / 20mm)

! Digital pistol grip bore gauges XT GROOVE for measuring special groove profiles, single devices, tungsten carbide-tipped measuring faces and extensions on request.

! Please specify the dimensions according to the sketch viewable above. This data is required to enable us to prepare a quotation. Alternatively, you can also send us a workpiece drawing.

Technical Data

Size:	6-20/0,001/58/62mm Bluetooth
Article no.:	2510607b
Brand:	BOWERS
Manufacturer number:	SP-SXTH10M-BT-GRO
Accuracy:	0,004mm
Depth stops:	Ø 18/20/22/26/33mm
For groove depths:	1,25/1,5/2/2,5mm
For groove width:	1,5mm
Measuring depths:	58/62mm
Measuring force:	18-8N
Measuring range:	6-20mm/.25-.8 inch
Reading:	0,001mm/.00005 inch
Setting rings:	Ø 8/12,5/20mm
Weight:	2.7kg